



THE RAMCO CEMENTS LIMITED, GOVINDAPURAM WORKS - ARIYALUR



**24th NATIONAL
AWARD FOR
EXCELLENCE IN
ENERGY
MANAGEMENT**

**13th - 15th
SEPTEMBER - 2023**

PRESENTING TEAM MEMBERS:

ANAND SRIDHAR - DEPUTY MANAGER (PROCESS)

CHINNARASU – DEPUTY MANAGER (ELECTRICAL)

MUNEES THANGAM – ASSISTANT MANAGER (MECHANICAL)

- ❖ Founded in 1962 by **Shri P.A.C. Ramasamy Raja**
- ❖ **The RAMCO group** is a well known business conglomerate has grown to be a pioneer in different sectors like Cement, Software, Textiles etc.
- ❖ **5th Largest Cement Producer** in India with total installed capacity of **22 MTPA** located at 11 places throughout India.
- ❖ RAMCO also produces Ready Mix Concrete and Dry Mortar products, and operates one of the largest wind farms in the country

GROUP COMPANIES




THE RAMCO CEMENTS LIMITED



RAMCO INDUSTRIES LIMITED



RAMCO TEXTILES LIMITED




RAMCO SURGICAL COTTON MILLS LIMITED



RAMCO SYSTEMS LIMITED

RAMCO CEMENTS LEADERSHIP TEAM



Shri. P.AC Ramasamy Raja
Founder



Shri. Ramasubramania Raja
Former Chairman




Shri. Venketrama Raja
Managing Director



Mr. A.V. Dharmakrishnan
Chief Executive Officer



Mr. M. Srinivasan
Executive Director - Operations



Mr. Balaji. K. Moorthy
Executive Director - Marketing

- ❖ Unit Head – Mr. Madhusudan Kulkarni
- ❖ Head of Energy Management System – Mr. Ganesh Ram
- ❖ Designated Energy Manager – Mr. Jothiswaran (EM - 6869)
- ❖ Certified Energy Auditor – Mr. Vinoth Bharani (EA - 21278)

Presenting Team Members -


- S Anand - Deputy Manager (Process) – (EA - 35003/23)
- C Munees Thangam – Assistant Manager (Mechanical)
- A Chinnarasu - Deputy Manager (Electrical)



Mr. Madhusudan Kulkarni
SVP – Manufacturing



Mr. Ganesh Ram
SGM – E&I



- 5 INTEGRATED CEMENT PLANTS & 6 GRINDING UNITS
- ACROSS 5 STATES
- TOTAL CEMENT PRODUCTION CAPACITY OF 22 MTPA
- 5TH LARGEST CEMENT PRODUCER IN INDIA
- 1 READY MIX PLANT & 3 DRY MORTAR PLANTS
- 1 STATE OF THE ART RESEARCH & DEVELOPMENT CENTRE


OUR PRODUCT RANGE – RIGHT PRODUCT FOR RIGHT APPLICATION




**Ramco
Supercrete**




Ramco Supergrade



OPC 43 Infra




OPC 53 Infra




OPC 43 Grade




OPC 53 Grade




**Ramco Super
Steel**



Ramco Super Fast



Ramco Supercoast



Ramco Samudra



**Ramco Superfine
EFC**



**Karthik Super
Plus**

OUR PRODUCT RANGE – FOR BUILDING CONSTRUCTION



PLANT SPECIFICATIONS

RAMCO - ARIYALUR	CLINKER CAPACITY (MTPA)	COMMISSIONING YEAR	CEMENT CAPACITY (MTPA)
LINE-1	1.63	2008	5.50
LINE-2	1.98	2011	
Thermal Power Plant –66 MW (40+20+6 MW Turbines) with 3 Boilers of 85 TPH Steam generation			

- ✓ The Products manufactured at Ramco - Ariyalur are Ordinary Portland Cement (OPC) as per BIS & SLS Standards and Portland Pozzolona Cement (PPC) as per BIS Standards.

TECHNICAL SPECIFICATIONS – ARIYALUR UNIT



CRUSHER

MAKE: L&T
CAPACITY: 900 TPH



RAWMILL-1

TYPE: VRM
MAKE: LOESCHE
MODEL: LM-46.4
CAPACITY: 335 TPH

RAWMILL-2

TYPE: VRM
MAKE: FLSMIDTH
MODEL: ATOX-42.5
CAPACITY: 350 TPH




KILN-1

MAKE: FLSMIDTH
CAPACITY: 4200 TPD
3.95*61 m
5-Stage PH - ILC

KILN-2

MAKE: FLSMIDTH
CAPACITY: 5000 TPD
4.15*64 m
5-Stage PH - ILC



CEMENT MILL-1

TYPE: VRM
MAKE: LOESCHE
MODEL: LM-56.3
CAPACITY: 305
TPH (PPC)



CEMENT MILL-2

TYPE: ROLLER
PRESS & BALL
MILL
MAKE:
THYSSENKRUPP -
POLYSIUS
CAPACITY: 230
TPH (PPC)




PACKER



Nos: 4
MAKE: EEL INDIA
LTD
CAPACITY: 240
TPH

SALIENT FEATURES OF ARIYALUR UNIT

- We are ISO – 9001, 14001, 45001, 50001 Certified
- Online Cross-Belt analyzers for quality control at the Raw materials stage itself
- Modern X-ray methods – XRD & XRF for analyzing elemental and chemical composition
- State-of-the-art grinding Technology and 950 TPH Packing Plant with Auto- truck loader arrangement
- India's first Aluminum dome for Limestone storage
- Covered sheds for Additive & Fuel storage
- Energy efficient plant operation using RAMCO OPTIMA / BLENDX with consistent quality











❖ CII ENERGY BENCHMARKING FOR INDIAN CEMENT INDUSTRY – VERSION-5, 2021


ELECTRICAL SPECIFIC ENERGY CONSUMPTION – CEMENT (OVERALL)



❖ CII ENERGY BENCHMARKING FOR INDIAN CEMENT INDUSTRY – VERSION-5, 2021



❖ CII ENERGY BENCHMARKING FOR INDIAN CEMENT INDUSTRY – VERSION-5, 2021



❖ CII ENERGY BENCHMARKING FOR INDIAN CEMENT INDUSTRY – VERSION-5, 2021

Reason behind the trend:


TSR % has increased from 5.10% to 9.17% compared to last year

DESCRIPTION	INTERNATIONAL BENCHMARK	NATIONAL BENCHMARK	RAMCO-ARIYALUR (2022-23)
Specific Heat Consumption (Kcal/ Kg Clinker)	665	690	695
Specific Power Consumption (KWH/Ton of Cement)	56	56.10	76.14 (OPC) 67.19 (PPC)

Source of Benchmarking Data:

- ❖ National Benchmark – CII CEMENT INDUSTRY BENCHMARKING – VERSION-5, 2021
- ❖ International Benchmark – UNITED NATIONS INDUSTRIAL DEVELOPMENT ORGANISATION - BENCHMARKING REPORT FOR CEMENT INDUSTRY - 2014

ROADMAP TO ACHIEVE BENCHMARK



IMPLEMENTED ENCON PROJECTS SUMMARY – LAST 3 YEARS

Year	No of Energy saving projects	Investment (INR Million)	Electrical savings (Million kWh)	Thermal savings (Million Kcal)	Total Savings (INR Million)
FY 2020-21	10	1.39	2.80	44.37	18.21
FY 2021-22	13	4.78	3.07	-	18.95
FY 2022-23	18	0.466	1.06	-	8.67
<u>TOTAL</u>	<u>41</u>	<u>6.636</u>	<u>6.93</u>	<u>44.37</u>	<u>45.83</u>

IMPLEMENTED ENCON PROJECTS – FY 2020-21

S. No.	Name of Energy saving projects	Investments (INR Million)	Electrical Savings (Million Kwh)	Thermal Savings (Million Kcal)	Total Savings (Million Rs.)
1	Optimization of Raw material mix & fuel mix for clinkerization process	-	0.253	42.16	4.90
2	Cooler fans optimization	-	0.506	2.10	3.99
3	Grinding medium optimization in Cementmill-2	-	0.940	-	3.72
4	Cement mill roller edge welding to increase the roller life and improve the mill performance	-	0.608	-	2.41
5	Belt Conveyor Idle Run Hours study made and Logic modification done to reduce the idle hours	-	0.237	-	0.94

IMPLEMENTED ENCON PROJECTS – FY 2020-21

S. No.	Name of Energy saving projects	Investments (INR Million)	Electrical Savings (Million Kwh)	Thermal Savings (Million Kcal)	Total Savings (Million Rs.)
6	Bore-well Automation System - Operating bore-wells spread across 10KM circle through mobile SIM operated automation system and avoided overflow of tanks and vehicle movement	0.03	0.027	-	0.10
7	Feeding of limestone from crusher to ASR	0.80		0.11	1.10
8	Line-2 Nose ring cooling fan 55 KW,1500RPM MOTOR replaced with 55KW,1000RPM MOTOR	-	0.15		0.60
9	RPM Mines office Solar Power supply	0.38	0.005		0.05
10	ASR – 2 Power Cable Reeling Drum Analog Panel Modified to Drive Panel and Stall Torque Motor to Induction motor	0.18	0.10		0.40
TOTAL		1.39	2.80	44.37	18.21

IMPLEMENTED ENCON PROJECTS – FY 2021-22

S. No.	Name of Energy saving projects	Investments (INR Million)	Electrical Savings (Million Kwh)	Thermal Savings (Million Kcal)	Total Savings (Million Rs.)
1	20 MW ACC fan blade with hub replaced by energy efficient blade with hub (4 Sets)	2.65	0.633	-	4.44
2	AFR Saving in terms of coal mill run hours and usage in Line-1 (One hour per day)	-	0.33	-	2.31
3	Dry Handling of TPP ash in calciner firing in Line-1	0.20	0.648	-	4.54
4	LOSS matrix done for unloading belt conveyors and process equipment. PLC logic modified and idle hours reduced	-	0.213	-	1.49
5	Stage blinding of 40 MW condensate extraction pump (CEP)	0.20	0.06	-	0.42
6	Clinker silo extraction DPC motor rpm reducing work	0.25	0.25	-	0.18
7	Elevator feed air slide blower line actuator fixing work	0.12	0.277	-	0.19

IMPLEMENTED ENCON PROJECTS – FY 2021-22

S. No.	Name of Energy saving projects	Investments (INR Million)	Electrical Savings (Million Kwh)	Thermal Savings (Million Kcal)	Total Savings (Million Rs.)
8	Raw meal silo feed elevator vent line modification work	-	0.108	-	0.76
9	Ball mill Vent fan (260FN02) VFD Installation	0.80	0.198	-	1.39
10	Star – Delta Controller installation at Packing Plant Elevators	0.06	0.011	-	0.78
11	Permanent Star Connection for LT motors in Line-1 Raw mill & Coal mill circuit	-	0.058	-	0.41
12	Ball mill nip trap blower stopped (260BL03)	-	0.057	-	0.40
13	Dry handling of TPP Ash for calciner firing in Line-2	0.50	0.234	-	1.64
TOTAL		4.78	3.07	-	18.95

IMPLEMENTED ENCON PROJECTS – FY 2022-23

S. No.	Name of Energy saving projects	Investments (INR Million)	Electrical Savings (Million Kwh)	Thermal Savings (Million Kcal)	Total Savings (Million Rs.)
1	Modification of Nozzle blockage design in Cement mill-1	0.05	0.100	-	0.80
2	Line-2 false air arresting work	-	0.118	-	0.95
3	Line-1 false air arresting work	-	0.158	-	1.267
4	Reduction in idle run hours of coal unloading conveyors	-	0.117	-	0.936
5	Kiln inlet analyser probe – Cooling water pump idle run hours reduction	-	0.005	-	0.04
6	Jumbo bag system and elevator interlock – timing changed based on site observation	-	0.026	-	0.20
7	Silo extraction bin and silo bag filter interlock	-	0.008	-	0.06
8	Bag-filter Fan interlock minutes to be reduced from 20 min to 10 mins	-	0.017	-	0.138
9	Operate raw water pumps with level based level sensor	-	0.092	-	0.74

IMPLEMENTED ENCON PROJECTS – FY 2022-23

S. No.	Name of Energy saving projects	Investments (INR Million)	Electrical Savings (Million Kwh)	Thermal Savings (Million Kcal)	Total Savings (Million Rs.)
10	Replaced the damaged diaphragm kits & pipe lines at Mill floor	0.025	0.048	-	0.39
11	Optimisation of Ball Mill Performance through Complete Replacement of Grinding Media.	0.125	0.193	-	1.56
12	Elimination of chute jam at wobbler discharge by modifying chute	0.100	0.062	-	0.51
13	Installation of VFD for 100hp pump motor and LDR for tower lights at RPM mines to reduce the consumption of EB power.	0.060	0.060	-	0.49
14	Jumbo bag loading machine bag filter change	-	0.032	-	0.26
15	PP Elevator & screen interlock, cement silo and packer bag filter interlock	-	0.00019	-	0.00
16	Installation damper control at delivery point of CCR building AC duct.	0.004	0.0027	-	0.02
17	Bag cleaning device air-slide blower to bag brush modification	0.100	0.0278	-	0.22
18	Optimisation of Plant cooling water fan	0.002	0.011278	-	0.09
TOTAL		0.466	1.06	-	8.67


ENCON PROJECTS – 2023-24 (PLANNED)

S. No.	Title of Project	Electrical Savings (in Million kWh/Annum)	Thermal Savings (in Million Kcal/Annum)	Investment (in Million Rs./Annum)
1	Cooler mid-air tapping to be done and to be used for Raw mill	3.15	-	20
2	Implementation of recommended CFD changes in Line-2 to reduce the pressure drop and Preheater (ID Fan) power consumption	0.58	6.60	20
3	Installation of MVAC Drive in RAW Mill -1 Fan	2.40	-	18.50
4	Removal of damper and replacement of bag filter fan in old crusher	0.06	-	-
5	Installation of VFD in raw water pump	0.01	-	0.50
6	Optimization of compressed air pressure in TPP	0.04	-	-
7	Installation of MVAC Drive in Preheater Fan -1	0.974	-	9.70
TOTAL		7.214	6.60	68.70

Project Title: REPLACEMENT OF VIBROFEEDER WITH REJECT BASED LOAD HANDLING SYSTEM IN RAW MILL-1

Project Description:

As per Loesche (OEM) design, vibro-feeder is present at the mill reject circuit and material from the vibro-feeder is then uniformly fed to the conveyor and followed by elevator to transport the material to reject bin. We have modified this design and replaced the vibro-feeder with VFD operated load based reject handling system.




Trigger for implementing the project:

Due to high limestone moisture, vibro-feeder coating was frequent, leading to unplanned mill stoppages and man power has to be used to remove the hard coating. Raw mill section availability was critically affected due to this persistent issue.


Why this is innovative?

Original design has been modified due to the problem caused by high moisture in limestone. After this modification, no stoppage has occurred due to this issue.

BEFORE



AFTER



Replication Potential:

It can be replicated for the plants having Loesche mill facing the same issue of coating formation due to high moisture in raw material.

Tangible Benefits:

- ❖ Annual savings of Rs.1.15 Lakhs per annum is achieved against the initial investment of Rs. 2 Lakhs
- ❖ Completely avoided mill stoppage due to coating formation in reject circuit
- ❖ Saving of 0.10 Kwh/Ton of material

Intangible Benefits:

- ❖ Improved mill availability and increased productivity
- ❖ Frequent loading of scrapper has been avoided
- ❖ Frequent cleaning of vibro-feeder has been avoided



PARTICULARS	BEFORE	AFTER
Coating Formation Tendency	Frequent	No Coating formation
Average number of mill stoppages per month	5	Nil



Project Title: REPLACEMENT WITH ENERGY EFFICIENT TURBINE IN THERMAL POWER PLANT

Project Description:

In order to reduce the specific steam consumption in the 40 MW turbine, we have decided to retrofit the turbine and approached our turbine OEM M/s. Siemens for upgrading the turbine with high efficiency.

Trigger for implementing the project:

Our specific steam consumption increased up to 4.20 Tons /MW against the design of 4.13 Tons /MW leading to more operating cost and fuel consumption. Therefore we proposed retrofit of the existing turbine to OEM and increase the operating efficiency.

Why this is innovative?

With the same casing of the turbine and without any changes in gearbox and generator, turbine has been modified and number of stages has been increased from 18 to 25. This design modification was implemented along with OEM.




RETROFITTED 40MW TURBINE

Replication Potential:

It can be replicated for the plants having high specific steam consumption in turbines.

Tangible Benefits:

- ❖ Annual savings of Rs.380.16 Lakhs per annum is achieved against the investment of Rs. 7.83 Crores.
- ❖ Heat rate of the turbine reduced from 2525 Kcal/kWh to 2400 Kcal/kWh.
- ❖ Return of Investment is 1.89 years
- ❖ Specific steam consumption of the old turbine is 4.20 Tons/MW, but the design upgraded new turbine’s specific steam consumption is only 3.97 Tons/MW.



Intangible Benefits:

- ❖ Due to low steam consumption by the turbine, steam generation in the boiler is reduced, thereby achieving savings in fuel consumption.



PARTICULARS	BEFORE	AFTER
Specific Steam Consumption	4.20 Tons/MW	3.97 Tons /MW
Turbine Heat Rate	2525 Kcal/kWh	2400 Kcal/kWh
Turbine Efficiency	34 %	36 %
No. of Stages in Turbine	18	25

Project Title: STAGE BLINDING IN 40 MW STG CONDENSATE EXTRACTION PUMP

Project Description:


Condensate extraction pump is present at the outlet of Condensate tank and is used to pump the condensate to the deaerator tank. Since the head developed by the pump is found to be higher, it was decided to reduce the head developed by the pump by reducing the impeller stages. During the overhauling of CEP pump, we have blinded two stages of the impellers with blind bush and blind sleeve.

Trigger for implementing the project:

At present, pressure developed by the CEP at the discharge is 16 Kg/cm² which is then reduced to 8 Kg/cm² with the help of pressure control valve on auto mode. This leads to higher power consumption and it was decided to reduce the pump head through modifications in impeller.

Why this is innovative?

Without affecting the pump discharge pressure and flow, we have removed two impeller stages from the pump and replaced with two blind bushes and sleeves. Impeller design has been modified based on the plant conditions.



Original design of CEP from OEM



Condensate Extraction Pump (CEP)



In-house Modified Design with removal of Two stages of impeller and replaced by blind bush and blind sleeve

Replication Potential:

It can be replicated in any multi-stage pumps operating in higher pressure and flow controlled mode of operation.

Almost 50% reduction in power consumption of CEP after modification

Tangible Benefits:

- ❖ Annual savings of Rs.18 Lakhs per annum is achieved against the investment of Rs. 5 Lakhs
- ❖ Power consumption of pump reduced from 99 kwh to 56 kwh. (43 units saved per hour)

PARTICULARS	BEFORE	AFTER
Impeller Stages	5	3
Pressure developed by CEP	16 Kg/cm2	8 Kg/cm2
Pressure control valve position	50 %	Full Open
Volumetric Flow	132 m3/hr	132 m3/hr
CEP Power Consumption	99 Kwh	56 Kwh

Intangible Benefits:

- ❖ Wear and tear of control valve is saved due to valve kept always in full open condition.
- ❖ Operation flexibility of pump at various load combination and power savings is achieved.



Onsite Generation				
Year	Technology (solar/wind/biomass etc)	Installed Capacity (MW)	Consumption (million kWh)	% of overall electrical energy consumption
FY 2020-21	SOLAR	0.054	0.03	-
FY 2021-22		0.054	0.03	-
FY 2022-23		0.065	0.04	-
Offsite Generation				
Year	Technology (solar/wind/biomass etc)	Installed Capacity (MW)	Consumption (million kWh) – allotted for plant	% of overall electrical energy consumption
FY 2020-21	WIND	153	-	-
FY 2021-22			-	-
FY 2022-23			-	-

- Out of the total installed capacity, **57.30 MW** has been allotted for Ariyalur plant and **Wind wheeling** has been started in current Financial Year

WASTE UTILIZATION AND MANAGEMENT

WASTE UTILISED AS FUEL				
S. No	Waste as fuel	Quantity (Tons)	GCV (Kcal/kg)	Waste as percentage of total fuel
1	ALTERNATE FUEL - LIQUID MIX	2479.55	1800	0.20
2	ALTERNATE FUEL - HARD PLASTIC & RUBBER COMPOSITE GRANULES, SIZE: <= 5 MM	2588.129	4400	0.50
3	ALTERNATE FUEL SOILID WASTE	13126.183	1500	0.86
4	ALTERNATE FUEL- PAINT PIGMENTS	247.48	1500	0.02
5	ALTERNATE FUEL - PRODUCTION ASH WASTE	32.78	2000	0.00
6	ALTERNATE FUEL LIQUID MIX - SPENT WASH	37.25	400	0.00
7	ALTERNATE FUEL - SHREDDED FOAM AND RUBBER	1457.506	5050	0.32
8	ALTERNATE FUEL - SHREDDED RDF 40-60 MM	13290.041	2000	1.17
9	ALTERNATE FUEL - SHREDDED TYRE .	464.741	6500	0.13
10	Raw Mill/ Kiln	196	4600	0.04
11	ALTERNATE FUEL WOODCHIPS .	4006.81	3000	0.53
12	COAL ASH – POWER PLANT	26167.138	2500	2.87
13	ALTERNATE FUEL WASTE PLASTIC RUBBER .	2205.93	2000	0.19
14	ALTERNATIVE FUEL - MLP WASTE	2,489.14	2000	0.22
15	ALTERNATE FUEL - DIP PLASTIC WASTE	697.537	2000	0.06
16	ALTERNATE FUEL CARBON BLACK	107.789	5800	0.03
17	ALTERNATE FUEL - MANGO SEED	9070	4000	1.59
18	ALTERNATE FUEL RICE HUSK .	2892.013	3200	0.41
19	ALTERNATE FUEL - RESIDUES OF STARCH	142.675	3600	0.02
20	ALTERNATE FUEL - SHREDDED COIR WASTE	75	4749	0.02

81773 Tons of AFR used and achieved 9.1% TSR in FY 22-23

WASTE UTILISED AS RAW MATERIAL			
Sl No	Waste as Raw material	Quantity (MT)	Name of raw material getting replaced
1	Slag	28271	Laterite & Fe-rich Limestone

- For quality correction in the raw mix, laterite was being used earlier which is now replaced by Slag from Steel industry as alternative raw material
- Utilization of waste from other industry as a raw material
- Cost effectiveness due to this replacement apart from natural raw material conservation

Total Fe rich Limestone replaced- 75201 Tons & Total Laterite replaced – 37600 Tons based on Iron correction

- ❖ 1 Shredder – 30 TPH Capacity
- ❖ Closed shed for storage of shredded AFR
- ❖ Weigh Bridge for AFR pre-processing
- ❖ Chain conveyor for conveying AFR to shredder
- ❖ Double flap gate at AFR discharge point at Preheater
- ❖ Dedicated Wheel loaders and tippers for AFR system
- ❖ Separate shredder for processing colony waste
- ❖ Apart from usage of AFR in Pyro-section in both lines, AFR usage also started in our Thermal Power Plant with dedicated over-feeding system




Storage yard



Shredder



Shredded AFR




AFR Feeding System



Conveying System



Shredder Rotor



❖ GHG EMISSIONS IN Kg CO2 / Ton of PPC

GHG EMISSION REDUCTION GOALS


Short Term Goal:

- Effective energy reduction measures in operations
- Continuous Green belt development
- Increased production of Blended cement
- Usage of E-vehicles for transportation inside the plant premises
- Power wheeling from Wind farms to plant

Long Term Goal:

- Reduction of nearly **31000 Tons of CO2 emission per year** by proposed renewable energy utilization including solar power and wind wheeling of power to cement plant from our wind farms.
- Large scale green belt development in plant, mines and all surrounding villages with the aim of planting **15000 trees per year**.
- To achieve 20% TSR in Kiln by effective utilization of AFR which will help us reduce nearly **1.50 Lakh Tons of CO2 emission per year**.

FACTORY GREEN BELT DETAILS



GREEN BELT DEVELOPMENT



REDUCTION OF GHG EMISSIONS BY GREEN SUPPLY CHAIN

- ❖ Reverse Logistics Methodology: Utilization of Gypsum and Fly-ash trucks as clinker / cement trucks and Cement Bulker respectively
- ❖ Utilization of Cement / clinker trucks as raw material trucks
- ❖ Increased usage of Rail transportation for clinker and cement which is both cost effective and faster compared to other modes.


2022-23	
INTER-UNIT CLINKER TRANSPORT THROUGH RAIL	448938 Tons (92% of total Clinker transport)
CEMENT TRANSPORT THROUGH RAIL & BULKERS	806304 Tons (30% of total Cement Dispatch)
CEMENT DISPATCH THROUGH JUMBO BAGS	20361 Tons




INTER-UNIT CLINKER TRANSPORT BY RAIL



CEMENT TRANSPORT BY RAIL





EXISTING ENERGY MANAGEMENT SYSTEM:

- Daily monitoring of plant energy consumption and addressing of deviations
- Weekly Energy Conservation Meeting
- Monthly meeting with technical team – Section-wise Energy KPI
- Weekly EnMS core team members of each section




ENERGY REVIEW MEETING – CHAIRED BY UNIT HEAD



ENERGY CONSERVATION TEAM – WEEKLY REVIEW MEETING

ISO 9001:2015



फॉर्म III (स्कیم-III) के पैरा 3 के उप-पैरा (5) को देखें।
Form III (Refer Sub-Para (5) of Para 3 of Scheme III)

भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS

गुणवत्ता प्रबंध पद्धति प्रमाणन लाइसेंस
LICENCE FOR THE QUALITY MANAGEMENT SYSTEMS CERTIFICATION

राष्ट्रीय उत्पाद मानक द्वारा को. नई दिल्ली द्वारा प्रत्यायित
(Accredited by National Accreditation Board for Certification Bodies, New Delhi)

संकेत नं. एन. QML-6006947-3
Licence No. QML-6006947-3

1. लाइसेंस मानक ब्यूरो अधिनियम, 2016 (2016 नं. 11) द्वारा प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the
Bureau hereby grants/recertifies to
4. समस्त भारत में।
All India




सीएचएसएम वर्क्स, सेंदुरई रोड,
अरियालूर तालुक, तमिलनाडु - 621 713
Sri Chinnivasan Works, Sengurai Road,
Ariyalur Taluk, Tamilnadu - 621 713

2. यह लाइसेंस इस लाइसेंस के विनियमन के अन्तर्गत प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the Bureau
hereby grants/recertifies to
4. समस्त भारत में।
All India

3. यह लाइसेंस 10 अक्टूबर 2020 से 09 अक्टूबर 2023 तक वैध होगा और इसका विनियमन के अनुसार नवीकरण किया जा
This licence shall be valid from 10 October 2020 to 09 October 2023 and may be renewed as
prescribed in the Regulations.

2021 के सेप्टेम्बर माह के 13 दिनांक पर हस्ताक्षरित
Signed, Sealed and Dated this 13th day of September 2021


उप-निदेशक (दक्षिणी क्षेत्र)
(U. S. P. YADAV)
Deputy Director General (Southern Region)
for BUREAU OF INDIAN STANDARDS
Southern Regional Office
Post Box No. 9290, C.I.T. Campus
IV Cross Road, Taramani, Chennai - 600 113.

MSC -F6-23 Issue - 04

Page 1 of 2

ISO 45001:2018



फॉर्म III (स्कیم-III) के पैरा 3 के उप-पैरा (5) को देखें।
Form III (Refer Sub-Para (5) of Para 3 of Scheme III)

भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS

राष्ट्रीय उत्पाद मानक द्वारा को. नई दिल्ली द्वारा प्रत्यायित
(Accredited by National Accreditation Board for Certification Bodies, New Delhi)

संकेत नं. एन. QML-6006947-3
Licence No. QML-6006947-3

1. लाइसेंस मानक ब्यूरो अधिनियम, 2016 (2016 नं. 11) द्वारा प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the
Bureau hereby grants/recertifies to
4. समस्त भारत में।
All India




सीएचएसएम वर्क्स, सेंदुरई रोड,
अरियालूर तालुक, तमिलनाडु - 621 713
Sri Chinnivasan Works, Sengurai Road,
Ariyalur Taluk, Tamilnadu - 621 713

2. यह लाइसेंस इस लाइसेंस के विनियमन के अन्तर्गत प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the Bureau
hereby grants/recertifies to
4. समस्त भारत में।
All India

3. यह लाइसेंस 10 अक्टूबर 2020 से 09 अक्टूबर 2023 तक वैध होगा और इसका विनियमन के अनुसार नवीकरण किया जा
This licence shall be valid from 10 October 2020 to 09 October 2023 and may be renewed as
prescribed in the Regulations.

2021 के सेप्टेम्बर माह के 13 दिनांक पर हस्ताक्षरित
Signed, Sealed and Dated this 13th day of September 2021


उप-निदेशक (दक्षिणी क्षेत्र)
(U. S. P. YADAV)
Deputy Director General (Southern Region)
for BUREAU OF INDIAN STANDARDS
Southern Regional Office
Post Box No. 9290, C.I.T. Campus
IV Cross Road, Taramani, Chennai - 600 113.

MSC -F6-23 Issue - 04

Page 1 of 2

ISO 14001:2015



फॉर्म III (स्कیم-III) के पैरा 3 के उप-पैरा (5) को देखें।
Form III (Refer Sub-Para (5) of Para 3 of Scheme III)

भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS

पर्यावरण प्रबंध पद्धति प्रमाणन लाइसेंस
LICENCE FOR THE ENVIRONMENTAL MANAGEMENT SYSTEMS CERTIFICATION

राष्ट्रीय उत्पाद मानक द्वारा को. नई दिल्ली द्वारा प्रत्यायित
(Accredited by National Accreditation Board for Certification Bodies, New Delhi)

संकेत नं. ईएम/L-6000582.2
Licence No. EM/L-6000582.2

1. लाइसेंस मानक ब्यूरो अधिनियम, 2016 (2016 नं. 11) द्वारा प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the Bureau
hereby grants/recertifies to
4. समस्त भारत में।
All India




सीएचएसएम वर्क्स, सेंदुरई रोड,
अरियालूर तालुक, तमिलनाडु - 621 713
Sri Chinnivasan Works, Sengurai Road,
Ariyalur Taluk, Tamilnadu - 621 713

2. यह लाइसेंस इस लाइसेंस के विनियमन के अन्तर्गत प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the Bureau
hereby grants/recertifies to
4. समस्त भारत में।
All India

3. यह लाइसेंस 10 अक्टूबर 2020 से 09 अक्टूबर 2023 तक वैध होगा और इसका विनियमन के अनुसार नवीकरण किया जा
This licence shall be valid from 10 October 2020 to 09 October 2023 and may be renewed as
prescribed in the Regulations.

2021 के सेप्टेम्बर माह के 13 दिनांक पर हस्ताक्षरित
Signed, Sealed and Dated this 13th day of September 2021


उप-निदेशक (दक्षिणी क्षेत्र)
(U. S. P. YADAV)
Deputy Director General (Southern Region)
for BUREAU OF INDIAN STANDARDS
Southern Regional Office
Post Box No. 9290, C.I.T. Campus
IV Cross Road, Taramani, Chennai - 600 113.

MSC -F6-23 Issue - 04

Page 1 of 2

ISO 50001:2018



फॉर्म III (स्कیم-III) के पैरा 3 के उप-पैरा (5) को देखें।
Form III (Refer Sub-Para (5) of Para 3 of Scheme III)

भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS

ऊर्जा प्रबंध पद्धति प्रमाणन लाइसेंस
LICENCE FOR THE ENERGY MANAGEMENT SYSTEMS CERTIFICATION

संकेत नं. ईएम/L-6000078.2
Licence No. EN/L-6000078.2

1. लाइसेंस मानक ब्यूरो अधिनियम, 2016 (2016 नं. 11) द्वारा प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the Bureau
hereby grants/recertifies to
4. समस्त भारत में।
All India




सीएचएसएम वर्क्स, सेंदुरई रोड,
अरियालूर तालुक, तमिलनाडु - 621 713, भारत।
Sri Chinnivasan Works, Sengurai Road,
Ariyalur Taluk, Tamilnadu - 621 713, India.

2. यह लाइसेंस इस लाइसेंस के विनियमन के अन्तर्गत प्रदान की गई शक्तियों के अन्तर्गत, ब्यूरो
By virtue of the power conferred on it by the Bureau of Indian Standards Act 2016 (11 of 2016), the Bureau
hereby grants/recertifies to
4. समस्त भारत में।
All India

3. यह लाइसेंस 08 जून 2023 से 23 मार्च 2026 तक वैध होगा और इसका विनियमन के अनुसार नवीकरण किया जा
This licence shall be valid from 08 June 2023 to 23 Mar 2026 and may be recertified as prescribed in
the Regulations.



जून 2023 के 28 तारीख को हस्ताक्षरित एवं मुहरांकित।
Signed, Sealed and Dated on 28th day of June 2023

उप-निदेशक (दक्षिणी क्षेत्र)
(U. S. P. YADAV)
Deputy Director General (Southern Region)
for BUREAU OF INDIAN STANDARDS
Southern Regional Office
Post Box No. 9290, C.I.T. Campus
IV Cross Road, Taramani, Chennai - 600 113.

MSC -F6-4-17 Issue - 02

Page 1 of 2



RAMCO OPTIMA EXPERT OPTIMIZER



RAMCO OPTIMA BLENDING CONTROL SYSTEM - BLENDX


- ❖ Dedicated Energy monitoring system designed by Greenergy to monitor section-wise energy consumption, load distribution pattern, critical electrical parameters, generation of daily power report and section-wise idle run hours monitoring.
- ❖ Continuous monitoring of KPIs like Specific Power and Heat Consumption
- ❖ Energy efficient plant operation with RAMCO OPTIMA EXPERT OPTIMIZATOIN SYSTEM and OPTIMA BLENDING CONTROL SYSTEM (BLENDX) for Quality Control

GREEN-CO CERTIFICATION:

- RAMCO-ARIYALUR unit has submitted the required details and pre-assessment is to done

LEARNINGS FROM CII AWARD PROGRAM:

- ❖ Latest trends in the cement industry
- ❖ Inspiration to achieve excellence in Energy Efficiency
- ❖ Technical Knowledge sharing among the peers
- ❖ Innovative ideas shared by the participants are encouraging us to develop new ideas
- ❖ Implementation of ENCON projects presented in CII by other companies which has potential of improvement in our unit



NET ZERO COMMITMENT – RAMCO SUSTAINABILITY TIMELINE

GOAL

Commitment to transition to Low Carbon Growth by investing in innovative technological solutions

Activities	Year 1	Year 2	Year 3	Year 4
Net Zero Carbon emissions	<ul style="list-style-type: none"> Explore opportunities to replace coal with biomass in Thermal Power Plant (TPP) Open access (PPA)/Group Captive option in Kolaghat and Vizag Grinding Units Establish Scope 3 emission baseline (Scope 3 accounting) Options for utilizing biofuels in process or utilities to be explored Tie up with NGO/ agricultural communities to take back agro waste that can be utilized as alternate fuels 	<ul style="list-style-type: none"> Energy optimization initiatives as planned in integrated units Reduce scope 3 emissions by 5% (e.g. switch to biodiesel in logistics, route optimization, green logistics policy etc.) 	<ul style="list-style-type: none"> Adoption of Energy efficiency initiatives in TPP and use of advanced automation system in the process (Alathiyur and RR Nagar) Reduce scope 3 emission by 10% 	<ul style="list-style-type: none"> Adoption of Energy efficiency initiatives in TPP and use of advanced automation system in the process (Ariyalur and Jayantipuram) Reduce scope 3 emission by 15% Alignment to SBTi & TCFD Carbon offsets - installation of solar lanterns, fuel efficient cook stove, LED Street lights etc to communities



- Electric vehicle for site visit by employees
- Employee commute from township to factory in bicycle
- Battery operated Forklift inside the stores building
- Electric vehicle for material shifting purpose





THE RAMCO CEMENTS LIMITED, ARIYALUR

Material Conservation & Waste Management Policy

The Ramco Cements Limited, Govindapuram places highest values for environmental protection and by incorporating principles of sustainable development in our activities towards material conservation, green supply chain and waste management by striving to achieve: -

- Effective Limestone management to conserve natural resources thereby increase mining life.
- Conservation of our natural resources and minimizing environmental impacts, thereby motivating the suppliers towards green supply chain.
- Encouraging our critical vendors / suppliers to adopt green supply chain practice.
- Increased usage of industrial wastes in cement manufacturing.
- Utilization of alternate fuels and raw materials.
- Reduction in packaged cement by promoting bulk cement.
- Adopting technology to increase the life of the consumables.
- Train and develop skill in all employees related to conservation & use.

Date: 12.05.2022

Unit Head
Madhusudan Kulkarni


WASTE MANAGEMENT & MATERIAL CONSERVATION POLICY

COLONY SOLID WASTE MANAGEMENT

- ❖ Collection of waste from colony
- ❖ Segregation of colony waste at shed
- ❖ Collection of municipality waste followed by segregation
- ❖ Transfer of segregated waste to AFR feeding area
- ❖ Feeding of segregated colony waste to shredder
- ❖ Utilization of colony waste in AFR

BIOGAS FROM FOOD WASTE

- ❖ Kitchen and Food wastes from colony & canteen are segregated. In colony block to block collections are being done.
- ❖ The collected waste are being used in the bio gas plant. It has an installed capacity of 400 kg/day to convert waste to bio gas.









Food waste utilized in biogas plant- FY : 31.82 MT











THE RAMCO CEMENTS LIMITED, ARIYALUR COMMITMENT TOWARDS EMPLOYEE INVOLVEMENT, COMPLETE SAFETY AND OVERALL HOLISTIC DEVELOPMENT	
KAIZEN PROJECTS IMPLEMENTED (2022-23)	65
QUALITY CIRCLE PROJECTS IMPLEMENTED (2022-23)	12
SUGGESTIONS RECEIVED IN OUR UNIT SUGGESTION SCHEME (2022-23)	332
SUGGESTIONS IMPLEMENTED (2022-23)	275
SAFETY CAMPAIGNS CONDUCTED	7
BEST SAFETY PERFORMER AWARDS	3
SAFE MAN HOURS ACHIEVED TILL MARCH-2023	27 Million Man Hours



EMPLOYEE INVOLVEMENT – FEW OF OUR KAIZEN PROJECTS

KAIZEN THEME	IDEA/COUNTER MEASURE	PROBLEM	BEFORE	AFTER
Elimination of fine material spillage from apron feeder	Installation of conveyor belt around the pan plate	<ul style="list-style-type: none"> ❖ While material feeding through the apron feeder, material got spillage throughout the equipment. ❖ Daily basis we need to clean the spillage material with 2 manpower's/day. ❖ Also fire hazard occurred in that place. 		
To ensure safe work for LSR-2 chute cleaning	Movable and removable type hand rails arrangements provided.	<ul style="list-style-type: none"> ▪ During in LSR operation, discharge chute getting jam and needs to cleaning. ▪ Discharge chute in open condition without hand rails. <ul style="list-style-type: none"> ▪ It has created unsafe condition. 		
ELIMINATION OF FIRE HAZARD IN LINE-2 AFR	PROVING NRV WITH RECEIVER TANK IN SHUTOFF GATE	If power failure happened, shutoff gate not closed properly due to compressed air pressure low. So fire hazards has occurred.		

EMPLOYEE INVOLVEMENT - FEW OF OUR KAIZEN PROJECTS

KAIZEN THEME	IDEA/COUNTER MEASURE	PROBLEM	BEFORE	AFTER
Elimination of 125BC10 discharge chute jam	Installation of air blaster in discharge chute	<ul style="list-style-type: none"> ❖ 125bc10 belt conveyor feeding the limestone to raw material hopper from LSR. ❖ If lime stone discharge on the belt conveyor, material got jammed & material has spilled in discharge chute of the belt conveyor. 		
Reduction of breakdown hours in raw mill-2 chain elevator	Installation of flange in bolt fixing portion and back side plate replacement.	<ul style="list-style-type: none"> ❖ Line-2 raw mill reject chain elevator bucket bolt locking area plate getting damage. ❖ While bucket damage, reject hopper got jammed and bucket has damaged the other buckets and boot level switch. 	 Bolt fixing area getting damage condition	 Bucket flanges provided
REDUCTION OF GEAR BOX LEADING TIME	Fabricated structure with roller arrangement	During replacement of main gear box, leading time has taken high and also more man power required for operating the chain blocks.		
Reduction of maintenance time for raw mill table internals inspection work	Installation of new small size door.	<ul style="list-style-type: none"> ❖ In Every maintenance we need to inspect the mill table inside bolts condition ❖ So we required to open the large size door. ❖ It will take more time to open & close the same. 		



Green Champion Award for the year 2021 for Ariyalur district.



CII EHS - SR Excellence Award



APEX INDIA FOUNDATION – PLATINUM AWARD FOR OCCUPATIONAL HEALTH AND SAFETY CATEGORY




CSRBOX award for the WASH category



Best CSR impact award -UBS forum



AWARD OF HONOR - National Safety Council, Tamilnadu Chapter



Anand Sridhar – 9043512483 – sanand@ramcocements.co.in
Chinnarasu – 9942342640 – chinnarasu@ramcocements.co.in
Munees Thangam – 9688396655 – muneesthangam@ramcocements.co.in